

DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DuPont [™] Krytox [®] PFPE Oils

Product Grade/Type : GPL: 100, 101, 102, 103, 104, 105, 106, 107, 107-500

VPF: 1506, 1514, 1520, 1525, 1525S, 1531, 1531E, 1618, 1645, 16256,

16350

CBF: 100A, 100B, 103B

GBO: 14, 25

XHT-: 500, 750, 1000 FG: 10, 12, 15, 40, 45

AUT 1045

4442, 4402, TFO, TLC, NBF140

TLF 8996 KDP-4885 Krytox ESP 250C Krytox SKY188 Zonyl 1045

MSDS Number : 150000000934

Product Use : Lubricant

Manufacturer : DuPont

1007 Market Street Wilmington, DE 19898

Product Information : 1-800-441-7515 (outside the U.S. 1-302-774-1000)
Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)

Transport Emergency : CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Other information : professional use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

The product as such is not hazardous. Inhalation of decomposition products from overheating may cause lung irritation or shortness of breath.



DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

Potential Health Effects

Skin

Perfluoroalkylether : May cause skin irritation.

May cause: Discomfort, itching, redness, or swelling.

Eyes

Perfluoroalkylether : May cause eye irritation.

May cause: Tearing, redness, or discomfort.

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by

IARC, NTP, or OSHA, as a carcinogen.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Perfluoroalkylether	60164-51-4	100 %

SECTION 4. FIRST AID MEASURES

Skin contact : Wash with water and soap as a precaution.

Eye contact : Rinse with plenty of water. If eye irritation persists, consult a specialist.

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or

combustion.

Ingestion : Never give anything by mouth to an unconscious person. DO NOT induce

vomiting unless directed to do so by a physician or poison control center.

General advice : When symptoms persist or in all cases of doubt seek medical advice.



DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

SECTION 5. FIREFIGHTING MEASURES

Flammable Properties

Flash point : Method : Pensky-Martens closed cup - PMCC

does not flash

Thermal decomposition : ca. 350 °C (662 °F)

Fire and Explosion Hazard : In fire conditions, toxic decomposition products may be formed. (see also

section 10)

Suitable extinguishing media : The product itself does not burn.

Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

Firefighting Instructions : Wear self-contained breathing apparatus (SCBA). Wear suitable protective

equipment.

Standard procedure for chemical fires.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Cleanup : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust).

Accidental Release Measures : Prevent material from entering sewers, waterways, or low areas.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel) : Avoid breathing vapors from overheated material.

General industrial hygiene practice.



DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

Storage : No special storage conditions required. Keep container closed to prevent

contamination.

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : In the event that the polymer is heated above 350 ℃ (662 °F), local ventilation

should be used to avoid exposure to fumes.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required. In the case

of hazardous fumes caused by overheating, wear self-contained breathing

apparatus.

Hand protection : Additional protection: No particular glove type is recommended, but nitrile

may used.

Eye protection : Safety glasses

Skin and body protection : No PPE is specified however, avoid contact with skin, eyes, and clothing.

Preventive skin protection

Exposure Guidelines Exposure Limit Values

Contains no substances with occupational exposure limit values.

None established.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : viscous, liquid
Color : colourless
Odor : none
pH : neutral

pour point : < -5 °C (23 °F)

Specific gravity : ca. 1.86 - 1.91 at 24 ℃ (75 ℉)

Water solubility : insoluble

4/7



DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

SECTION 10. STABILITY AND REACTIVITY

Stability : Stable under recommended storage conditions.

Conditions to avoid : Decomposition temperature 350 °C (662 °F)

Hazardous decomposition

products

: Hazardous thermal decomposition products:

Fluorinated compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Perfluoroalkylether

Dermal ALD - Approximate : ca. > 17,000 mg/kg , rabbit

Lethal Dose

Oral LD50

: > 37,400 mg/kg, rat

Inhalation 4 h ALC -

Approximate Lethal

Concentration

Skin irritation

: ca. > 19.54 mg/l, rat

slight irritation, rabbit

Eye irritation slight irritation, rabbit

Skin sensitization Patch test on human volunteers did not demonstrate sensitisation

properties., human

Mutagenicity Did not cause genetic damage in cultured bacterial cells.

Further information The substance is a polymer and is not expected to produce toxic

effects.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity Perfluoroalkylether

5/7



DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

96 h LC50 : Oncorhynchus mykiss (rainbow trout) > 1,000 mg/l

The substance is a polymer and is not expected to produce toxic

effects.

48 h EC50 : Daphnia magna (Water flea) > 1,000 mg/l

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : In accordance with local and national regulations.

Environmental Hazards : Dispose of container properly.

If recycling is not practicable, dispose of in compliance with local regulations.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

HMIS

Health : 1
Flammability : 0
Reactivity/Physical hazard : 0

PPE : Personal Protection rating to be

supplied by user depending on use



DuPont[™] Krytox[®] PFPE Oils

Version 4.1

Revision Date 07/09/2013 Ref. 150000000934

conditions.

Restrictions for use : Do not use DuPont materials in medical applications involving implantation

in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of the DuPont POLICY Regarding Medical Applications H-50103-3 and

DuPont CAUTION Regarding Medical Applications H-50102-3.

Krytox[®] and The DuPont Oval Logo[®] are trademarks of E. I. du Pont de Nemours and Company

Contact person : MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE

19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.